

 **WESTPOINT®**



CLIMATISEUR CASSETTE

**WESTPOINT**

Create emotions

CLIMATISEUR CASSETTE

CHAUD & FROID

Désignation		Unité	On/Off R22		INVERTER R410 a	
			WKT-48.LH	WKT-60.LH	WKIT-48.LH	WKIT-60.LH
Capacité	Mode Froid	Btu/h	48 000	60 000	48 000	60 000
		kW	14	18	14	18
	Mode Chaud	Btu/h	50 000	60 500	52 800	63 000
		kW	15	18	16	18
Alimentation d'énergie	Unité Interieure	V ~, Hz, Ph	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1
	Unité Exterieur	V ~, Hz, Ph	380-415,50,3	380-415,50,3	380-415,50,3	380-415,50,3
Consommation d'énergie	Mode Froid	W	4636	5694	4220	5450
	Mode Chaud	W	5 079	5 700	4 559	4 559
Performance	EER	W/W	3,02	2,83	3.32	3.21
	COP	W/W	3	3	3.52	3.38
	Circulation d'air intérieur	m3/h	1660	1700	1660	1700
Niveau de bruit	Unité Interieure (Hi/Med/Low)	dB(A)	47	50	47	50
	Unité Exterieur (Hi/Med/Low)	dB(A)	60	57	60	60
Dimensions	Unité Interieure (WxHxD)	mm	840x300x840	840x300x840	840x300x840	840x300x840
	Unité Exterieur (WxHxD)	mm	940x1250x340	940x1250x340	940x1250x340	940x1250x340
Poids net	Unité Interieure	kg	30	30	30	31
	Unité Exterieur	kg	93	101	93	98
Diamètre	Liquide / Gaz	mm	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")