



CLIMATISEUR CONVERTIBLE

**WESTPOINT**

Create emotions

CLIMATISEUR CONVERTIBLE

CHAUD & FROID

Désignation		Unité	On/Off R22			On/Off R410 a		INVERTER R410a	
			FLEXI-42.H	FLEXI-48.H	FLEXI-60.H	WFT-48.LH	WFT-60.LH	WFIT-48.LH	WFIT-60.LH
Capacité	Mode Froid	Btu/h	42 000	48 000	60 000	48 000	55 000	48 000	55 000
		kW	12	14	18	14	16	14	16
	Mode Chaud	Btu/h	42 840	48 960	61 200	50 000	60 500	53 000	63 000
		kW	12,5	14,3	17,9	14,65	17,73	15,53	18,4
Alimentation d'énergie	Unité Interieure	V ~, Hz, Ph	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1
	Unité Exterieur	V ~, Hz, Ph	220-240,50,1	220-240,50,1	380-420,50,3	380-415,50,3	380-415,50,3	380-415,50,3	380-415,50,3
Consommation d'énergie	Mode Froid	W	3900	4710	5450	4058	5147	4140	5500
	Mode Chaud	W	-	-	-	4551	5594	4438	5420
Performance	EER	W/W	-	-	-	3.08	2.88	3.38	3.18
	COP	W/W	-	-	-	3.61	3.44	3.50	3.39
	Circulation d'air intérieur	m3/h	1750	2160	2220	2177	2177	1800	2000
Niveau de bruit	Unité Interieure (Hi/Med/Low)	dB(A)	56	55	56	52	52	52	54
	Unité Exterieur (Hi/Med/Low)	dB(A)	-	-	-	60	57	60	60
Dimensions	Unité Interieure (WxHxD)	mm	1285x675x235	1650x675x235	1650x675x235	1635x675x235	1635x675x235	1635x675x235	1635x675x235
	Unité Exterieur (WxHxD)	mm	925x700x395	925x700x395	925x1150x395	940x1250x340	940x1250x341	940x1250x340	940x1250x340
Poids net	Unité Interieure	kg	32	40	42	38	41	38	41
	Unité Exterieur	kg	76	81	106	93	101	93	98
Diamètre	Liquide / Gaz	mm	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")	Ø12.7/Ø19.1 (1/2"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")	Ø9.52/Ø19.1 (3/8"/3/4")