



GAINABLE



WESTPOINT
Create emotions

CLIMATISEUR GAINABLE

CHAUD & FROID

			On/Off R22				
Désignation		Unité	WDT-48.H	WDT-60.H	WDA-48.H	WDA-60.H	WDA-70.H
Capacité	Mode Froid	Btu/h	48 000	60 000	49 000	60 100	69 400
		kW	14	17	14,43	17,62	20,35
	Mode Chaud	Btu/h	50 000	60 500	45 264	55 292	63 848
		kW	14,6	17,74	13,27	16,21	18,72
Alimentation d'énergie	Unité Interieure	V ~, Hz, Ph	380-415,50,3	380-415,50,3	220-240,50,1	220-240,50,1	220-240,50,1
	Unité Exterieure	V ~, Hz, Ph	380-415,50,3	380-415,50,3	220-240,50,1	380-420,50,3	380-420,50,3
Consommation d'énergie	Mode Froid	W	4 701	5 762	500	500	600
	Mode Chaud	W	4600	5191	–	–	–
Performance	EER	W/W	3	3	–	–	–
	COP	W/W	3,18	3,42	–	–	–
	Circulation d'air intérieur	m3/h	2 100	2 200	2 260	2 585	2 770
Niveau de bruit	Unité Interieure (Hi/Med/Low)	dB(A)	47	47	50	52	54
	Unité Exterieure (Hi/Med/Low)	dB(A)	60	60	–	–	–
Dimensions	Unité Interieure (WxHxD)	mm	1200x300x800	1200x300x800	1100x378x657	1100x378x657	1200x435x690
	Unité Exterieure (WxHxD)	mm	940x1250x340	940x1300x340	–	–	–
Poids net	Unité Interieure	kg	45	45	73	73	81
	Unité Exterieure	kg	99	103	81	109	109
Diamètre	Liquide / Gaz	mm	Ø12.7/Ø19 (1/2"/3/4")	Ø12.7/Ø19 (1/2"/3/4")	Ø12.7/Ø19 (1/2"/3/4")	Ø12.7/Ø22,22 (1/2"/7/8")	Ø12.7/Ø22,22 (1/2"/7/8")

**WESTPOINT**
Create emotions

CLIMATISEUR GAINABLE

CHAUD & FROID

Désignation		Unité	On/Off R410a			
			WDM-48.LH	WDM-60.LH	WDT-48.LH	WDT-60.LH
Capacité	Mode Froid	Btu/h	48 000	55 000	48 000	55 000
		kW	14,07	16,12	14	16,11
	Mode Chaud	Btu/h	55 000	60 000	50 000	60 500
		kW	16,12	17,58	14,65	17,73
Alimentation d'énergie	Unité Interieure	V ~, Hz, Ph	380-415,50,3	380-415,50,3	220-240,50,1	220-240,50,1
	Unité Exterieur	V ~, Hz, Ph	380-415,50,3	380-415,50,3	380-415,50,3	380-415,50,3
Consommation d'énergie	Mode Froid	W	5 350	6 360	4 560	5 694
	Mode Chaud	W	4815	5540	4446	4845
Performance	EER	W/W	3	3	3	3
	COP	W/W	3,35	3,17	3,3	3,66
	Circulation d'air intérieur	m3/h	2 200	2 400	2 100	2 200
Niveau de bruit	Unité Interieure (Hi/Med/Low)	dB(A)	45	46	44	45
	Unité Exterieur (Hi/Med/Low)	dB(A)	63	63	60	57
Dimensions	Unité Interieure (WxHxD)	mm	1200x300x874	1200x300x874	1405x375x925	1405x375x925
	Unité Exterieur (WxHxD)	mm	900x1170x350	900x1170x350	940x1250x340	940x1250x340
Poids net	Unité Interieure	kg	46	46	45	45
	Unité Exterieur	kg	93	97	93	101
Diamètre	Liquide / Gaz	mm	Ø9.52/Ø19.05 (3/8"/3/4")	Ø9.52/Ø15.9 (3/8"/5/8")	Ø9.52/Ø19.05 (3/8"/3/4")	Ø9.52/Ø19.05 (3/8"/3/4")



WESTPOINT
Create emotions

CLIMATISEUR GAINABLE

CHAUD & FROID

Désignation		Unité	INVERTER R410a				
			WDIA-36.LH	WDIA-42.LH	WDIA-48.LH	WDIT-48.LH	WDIT-60.LH
Capacité	Mode Froid	Btu/h	36000	42000	48000	48000	55000
		kW	10,5	12,3	14	14	16
	Mode Chaud	Btu/h	38000	46000	55000	50000	60500
		kW	11,13	13,48	16,12	14,65	17,73
Alimentation d'énergie	Unité Interieure	V ~, Hz, Ph	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1	220-240,50,1
	Unité Exterieur	V ~, Hz, Ph	380-420,50,3	220-240,50,1	380-415,50,3	380-415,50,3	380-415,50,3
Consommation d'énergie	Mode Froid	W	3965	4090	5115	4180	5420
	Mode Chaud	W	2923	3535	4355	4440	5460
Performance	EER	W/W	6,1	5,6	6,1	3,35	3,23
	COP	W/W	4	4	4	3,5	3,37
	Circulation d'air intérieur	m3/h	2156	2250	2330	2000	2200
Niveau de bruit	Unité Interieure (Hi/Med/Low)	dB(A)	48	50	50	47	49
	Unité Exterieur (Hi/Med/Low)	dB(A)	62	63	65	60	60
Dimensions	Unité Interieure (WxHxD)	mm	1200x300x865	1200x300x865	1200x300x865	1200x300x835	1200x300x835
	Unité Exterieur (WxHxD)	mm	946x810x410	946x810x410	952x1133x415	940x1250x340	940x1250x340
Poids net	Unité Interieure	kg	45	43.4	43.2	45	45
	Unité Exterieur	kg	78.9	70.5	108.1	93	98
Diamètre	Liquide / Gaz	mm	Ø9.52/Ø19.05 (3/8"/5/8")	Ø9.52/Ø15.9 (3/8"/3/4")	Ø9.52/Ø15.9 (3/8"/5/8")	Ø9.52/Ø19.05 (3/8"/5/8")	Ø9.52/Ø19.05 (3/8"/5/8")