

CLIMATISEUR MURAL INVERTER

18000 BTU



TROPICAL
Température extérieure 50°C



Jusqu'à 50% d'économie d'énergie



Super silencieux



Wi-Fi

Module WIFI



Kit de stérilisation UV



EN OPTION



économie d'énergie



Filtre multi-fonctions



Auto balayage



Froid rapide



Chauffage rapide



Ventilation confort



Mode Silence



Ecran LED

PERFORMANCES			
Cooling capacity		(Btu) (W)	18000 4910
Heating capacity		(Btu) (W)	18000 5280
STANDARD CONDITIONS			
Input power cooling		(W)	787
Input power heating		(W)	855
Running current cooling		(A)	3.8
Running current heating		(A)	4.3
Air flow	high auto medium	(m ³ /h) (m ³ /h) (m ³ /h)	835 560 450
Remote control			YES
Inverter			YES
Gas refrigerant			R410a
Charge		(g)	1400
E.E.R.		(W/W)	3.31
Voltage		IDU (V-Ph) ODU (V-Ph)	220-240 V - 1 PH 220-240 V - 1 PH
Frequency		(Hz)	50 Hz
FEATURES			
Indoor unit			
Net dimensions	height width depth	(mm) (mm) (mm)	319 965 215
Gross dimensions	height width depth	(mm) (mm) (mm)	410 1045 305
Net weight		(kg)	11.8
Gross weight		(kg)	15.2
Sound pressure	high medium low	(dB(A)) (dB(A)) (dB(A))	45.0 36.0 29.5
Excessive operating pressure	discharge suction	(MPa) (MPa)	4.2 1.5
Max current		(A)	13.5
Max power input		(W)	2650
Outdoor unit			
Net dimensions	height width depth	(mm) (mm) (mm)	554 800 333
Gross dimensions	height width depth	(mm) (mm) (mm)	625 920 390
Net weight		(kg)	34.9
Gross weight		(kg)	37,6
Air flow		(m ³ /h)	2000
Noise level		(dB(A))	53.5
Max current		(A)	13.5
Max power input		(W)	2650
Compressor type			ROTARY
Compressor brand			GMCC
Compressor model			ASN140D21UFZ
Connection pipe	mini length allowed maxi length allowed maxi height allowed diameter liquid gas connexion	(m) (m) (m) (mm) (inch) (mm) (inch)	3 30 20 6.35 / 1/4 " 12.7 / 1/2"
OPTIONS			
LED display			YES
Timer		(h)	24